


Centrifugalni ventilatori sa jednim usisom i Sirocco radnim kolom Single Inlet Centrifugal Fans With Forward Curved Blades (Sirocco Type)



Model	Snaga (Power)		Prirubnica na usisu (Inlet flange) Ø (mm)	Protok (Air flow) (m³/h)	Napon (Voltage) (V)	Cena (Price)
	(kW)	(HP)				
1.450 o/min (rpm)						
JHPS 0,25	0,18	0,25	120	380	220 / 380	178,00
JHPS 0,5	0,37	0,50	160	1.750	220 / 380	245,00
JHPS 0,5	0,37	0,50	180	2.550	220 / 380	267,00
2.800 o/min (rpm)						
JHPS 0,25	0,18	0,25	100	450	220	178,00
JHPS 0,25	0,18	0,25	120	780	220 / 380	178,00
JHPS 0,5	0,37	0,37	120	1.600	220 / 380	219,00
JHPS 0,75	0,55	0,55	140	2.500	220 / 380	231,00
JHPS 1,5	1,10	1,10	160	3.200	220 / 380	334,00
JHPS 2,0	1,50	1,50	180	3.500	220 / 380	425,00

**U PRODAJI DO ISTEKA ZALIHA. PRE PORUČIVANJA PROVERITE DOSTUPNOST SA PRODAVCEM.
IN OFFER UNTIL STOCK EXPIRATION. BEFORE ORDERING PLEASE CHECK AVAILABILITY WITH OUR SALES DEPARTMENT.**

- a) Pogodni su za laboratorije, restorane, radionice / Suitable for laboratories, restaurants, workshops.
- b) Kućište je od visokokvalitetnog presovanog lima, zaštićeno elektrostatičkim epoksnim bojama. / Housing made of high quality pressed steel sheet protected by electrostatic, epoxy paint.
- c) Visoko kvalitetan elektromotor specijalno projektovan za ventilatore; zaštita motora IP55-Klase F. Napajanje: 220V-50Hz ili 380V-50Hz. / High quality electric motor specially manufactured for fans; protection IP55-Class F. Input voltage: 220V-50Hz or 380V-50Hz.
- d) Standardno ofabrani u RAL boju. / Painted in RAL color as standard.
- e) Postoji mogućnost montaže u aeroboks; cene na upit. / Can be delivered within fan section; prices upon request.
- f) Regulisanje monofaznih modela se vrši reostatom (model 0,25 reostatom REM 2,5N; model 0,5 reostatom REM 5; modeli 0,75; 1,0; 1,5 i 2,0 reostatom REM 10). Za sve trofazne modele obavezna je regulacija frekventnim regulatorom. / Single phase models regulation with speed controller (model 0,25 with REM 2,5N; model 0,5 with REM 5; models 0,75; 1,0; 1,5 and 2,0 with REM 10). Three phase models must be driven with frequency inverter.

Sve cene su date bez uračunatog PDV / All Prices Are Given Without V.A.T.

