

Serija CMA(B/T)



Centrifugalni ventilatori sa jednim usisom, ventilaciono kolo sa unapred zakrivljenim lopaticama i napravljeno od galvanizovanog čelika. Aluminijumsko kućište (standardno LG) obojen epoksi bojom. Zaštitna mraža na usisu. Monofazni motor 230V-50Hz ili trofazni 230/400V-50Hz, sa 2 polova, IP55, klasa F. Za kontinualnu distribuciju čistog vazduha do 80°C.



Industrijske
mašine za
aspiraciju



CONTINUO

Na zahtev:
Dvobrzinski trofazni motor sa 2/4 pola.

Kod	Model	Broj/min	Snaga jedinice (kW)	Max. jačina struje (A)		Max. protok (m ³ /h)	Nivo šuma (dB(A))	Težina (kg)	Cena 2G
				230 V	400 V				
				5130261500	CMAB/2-108/42-0,03	2800	0,03	0,40	
5130261400	CMAT/2-108/42-0,05	2800	0,05	0,37	0,25	190	59	3,5	338,00
5130261700	CMAB/2-133/62-0,18	2800	0,18	1,75		685	69	6,6	429,00
5130261600	CMAT/2-133/62-0,18	2800	0,18	1,07	0,55	685	69	6,2	381,00
5130261900	CMAB/2-146/62-0,25	2800	0,25	1,93		780	70	6,5	443,00
5130261800	CMAT/2-146/62-0,25	2800	0,25	1,27	0,80	780	70	6,5	390,00
5130262100	CMAB/2-160/75-0,37	2820	0,37	2,90		1.130	71	9,0	579,00
5130262000	CMAT/2-160/75-0,37	2820	0,37	1,76	1,02	1.130	71	7,5	532,00
5130262300	CMAB/2-180/62-0,55	2820	0,55	4,00		1.200	77	10,0	584,00
5130262200	CMAT/2-180/62-0,55	2820	0,55	2,35	1,35	1.200	77	8,0	558,00
5130262500	CMAB/2-180/85-1,1	2820	1,10	7,00		2.300	79	10,0	831,00
5130262400	CMAT/2-180/85-1,1	2820	1,10	4,40	2,50	2.300	79	10,0	752,00
5130262700	CMAB/2-200/742-1,5	2820	1,50	10,00		2.660	80	22,0	895,00
5130262600	CMAT/2-200/74-1,5	2820	1,50	5,70	3,30	2.660	80	22,0	816,00
5130262800	CMAT/2-215/102-2,2	2820	2,20	8,40	4,60	2.920	82	28,0	985,00
5130263000	CMAT/2-225/104-3	2900	3,00	11,40	6,50	3.730	88	31,0	1542,00
5130263100	CMAT/2-250/114-5,5	2900	5,50		11,60	5.730	92	58,0	2254,00